







## **C-Tile 19''** Powered by the Chromebox Mini

A 19" 2-in-1 solution, which combines the Chromebox Mini with a touch display. This interactive solution is perfect for smart kiosks, room booking or checkin systems in different environments, such as retail, enterprises and schools. By integrating the Chromebox Mini and the screen, no extra cables are needed, which ensures a tamperproof solution for commercial environments.

C-Tile 19" features:

- Rockchip RK3288C Quad Core Cortex-A17 1.8GHz
- 19,5", 1920 x 1080 px, 250 nits, VA panel
- Fanless and solid-state
- Two-in-one solution

## C-Tile 19"





40.8 mm

Model name		AT19M-FRG	LAN/Wireless		Giga LAN x 1, 10/100/1000 Mbps Realtek RTL8211E with LED indicate Wi-Fi+ Bluetooth; WiFi 802.11 b/g/n/ ac + BT4.2
Description		19" all-in-one thin kiosk / POS / Interactive touch device			
Key Features		Front panel IP65 design, surface hard- ness: 7H, T2.4mm FHD panel, res. 1920 x 1080 PCT touch 10 points Fanless & design for 24/7 operation Built-in hidden dual and WiFi Antenna 2 x RJ50, support RS232	Storage		EMMC 5.0 16GB
			Side I/O		Reset button x 1 Kensington lock hole x 1 Power indicator x 1
Target Uses		Digital Signage / POS / Kiosk / Smart Vending	System I/O Thermal Design		DC 19V/20V Jack x 1 USB 2.0 Port x 4 RJ45 LAN Jack x 1 PC Legacy RS232 Serial Port x 2
Supported OS		Chrome OS			
CPU		iRockchip RK3288C Quad-Core Cortex-A17			through RJ50 Power button x 1
Chipset		Turbo up to 1.8GHz			Fanless
Device Management		CDM (Optional)	Adapter		40W 19V 2.1A
Security		Kensington Lock	Power		AC 100 ~ 240V
·		Google TPM Dual Channel LP DDR3 4GB	Operating Temperature		$0 \sim 40^{\circ}$ C (32 $\sim 104^{\circ}$ F)
Memory				Dimension (WxHxD mm)	492.6 x 306.6 x 40.8
Display and Video	Display	ARM Mali-T764 MP4 GPU @ 600 MHz	Physical Specification	Packaging	
	Resolution	15.6" 1920x1080 (16:9)		Dimension (WxHxD mm)	600 x 170 x 470
	Maximum Brightness	250 nits		Gross Weight	7.49 kg
	Display Orientation	Landscape / Portrait			<b>.</b>
	View Angle	178°/178°		Net Weight	6.06 kg
	Response Time (average)	25ms		Fan	No
	Contrast Ratio	3000:1		Housing Material	Metal
Touch Type		Projected Capacitive Touch, support 10 points touch Surface Hardness : 7H, 2.4mm		Colour	Black
			What's Included		
Front Camera		2M pixel (Optional)	AOPEN iC15F0 Power Cord/ Power Clip 40W (19V, 2.1A) AC Adapter Manual Push pin 3 years limited manufacterers commercial warranty		
Expansion		-			
Audio		Maxim MAX98090 Built-in stereo digital mic. and speaker 2W speaker			

Supports:





AOPEN also has a device management and application development platform, meldCX, please visit meldcx.com or ask your AOPEN Sales Rep for more information.



The specifications depicted may be subject to change without prior notice. All trademarks are copyright of their respective owners. © AOPEN Inc. All Rights Reserved.