

FLEXPOS

FlexPOS120/150 Touch POS Terminal



Specifications:

CPU	Intel Socket 370 Processors, Front Side Bus 66/100/133 MHz Pentium III (Tualatin) up to 1.26GHz, Celeron up to 1.3GHz	
LCD	12.1" TFT, 340 nits	15" TFT, 250 nits
Resolution	800 x 600 SVGA	1024 x 768 XGA
Touch Screen	RS-232 Interface, 5-Wire resistive, either ELO or E-Turbo	
System Chipset	Sis630ST	
System Memory	2 x 168pin DIMM socket for PC100/PC133 SDRAM, up to 1GB	
Watchdog Timer	64-level time intervals	
Graphics	Integrated VGA/LCD display controller, video memory up to 64MB(share from system memory) 2D/3D GUI engine, AGP 4X VGA, support dual display mirroring/multiple mode	
Audio/ Speaker	AC97 audec codec Built-in stereo speakers face to customer side	
Storage Device	- 1x 3.5" hard disk drive on pedestal - 1x slim type floppy disk drive on pedestal (option) - 1x Compact Flash type I/II socket on front panel left side	
Ethernet	10/100 Base-T fast Ethernet	
Wireless LAN	Internal 802.11g wireless LAN with antenna (option)	
Modem	Built-in 56K Modem module (option)	
I/O Ports	6 Serial ports, 4 free for optional devices use COM 4: RS-232/422/485 COM 1/5/6: RS-232 COM 2: reserved for IrDA COM 3: reserved for touch screen COM 1/4/5/6 with + 5V/12V power output on pin 9 1x Parallel port, 2x USB ports; 1x VGA port, 1x RJ-45 LAN port; 2x RJ-11 phone jack for Modem; 1x PS/2 keyboard connector; 1x PS/2 mouse connector 1x 12VDC Cash Drawer port(RJ-11) 1x external IDE port with +5/12VDC out	
LED Indicate	Power, LAN, HDD	
Backlight Adjustment	3 buttons (bright, dark, on/off)	
MSR	Tracks 1/2/3 card reader on front panel right side, internal PS/2 interface (option)	
USB PIN Key	USB interface PIN key on front panel left side (option), also available for USB devices	
Customer Display	FPS2002PD Pole Display, 2 Line 20 Character, RS232 Interface	
Terminal Peripheral	POS Printers, Scanners, Cash Drawers etc.	
Internal Power Supply	ATX 180W, input range 100~240VAC @ 50~60Hz	
Stand	Tilting angle -10°~85° for both desk-top and wall mount without additional parts	
Construction	Inside: heavy-duty steel; Outside: fire-proof resilient plastic (charcoal)	
Operating System	DOS, WIN 95/98/2000/XP/NT, XP Embedded	
Safety & EMI	FCC, CE, UL	
Dimensions	353(W)x323.7(H)x318(D) mm	367(W) x 323(H) x 348(D) mm
Weight	7.1kgs	8.1kgs

