

FLEXPOS

P-OPEN

Industrial Open-frame panel PC



System	AMD K7	Pentium 4
LCD Resolution	12.1": 800 x 600, 15": 1024 x 768, 17": 1280 x 1024 , 19": 1280 x 1024	
LCD Brightness	12.1": 350 nits, 15": 250 nits, 17": 300 nits, 19": 300 nits	
LCD Size	12.1", 15", 17" , 19"	
Touch Screen	5-wire Resistive, Surface Acoustic Wave Touch (option)	
Chipset	VIA KN400A + 8237R Plus	INTEL 845GV+ ICH4
Mainboard	Flex-623 (Rev:1.02)	Flex-845 (Rev:1.11)
CPU	Socket 462 processors FSB 66/100/133MHz , DDR400 AMD Geode NX1750(1.4G) /NX1500(1.0G)/ NX1250(667MHz)	Socket 478 processors FSB 400/533MHz , DDR333, Pentium® 4 up to 3.06GHz Celeron up to 2.5GHz
Memory	256MB – 1GB (1x 184-pin DDR)	256MB – 1GB (1x 184-pin DDR)
Display	Integrated VGA/LCD Controller, 2D/3D GUI engine, Sharing memory architecture up to 64 MB	
Drive Bays	1 x HDD 3.5", 1x Slim CD-ROM/DVD-ROM Drive, 1 x Slim FDD	
Compact Flash	Compact Flash socket type II (option)	Compact Flash socket type II (option)
Watchdog Timer	256-level intervals	
Ethernet	Onboard Realtek 8101L 10/100 LAN	
Audio	Onboard AC'97 Audio Codec (Line-in, Line-out & Mic-in)	
I/O Ports	4 x Serial (3 x RS232, 1x RS-232 / 422 / 485), +5V/12V power output on pin 9	
	1 x PS/2 Keyboard, 1 x PS/2 Mouse	
	1 x DIO (Input *2; Output *2) with 1 x RJ-11 Phone Jack	
	6x USB 2.0 (4 x back I/O, 2 x onboard)	6x USB 2.0 (4 x back I/O, 2 x onboard)
	1 x VGA Interface for second display , 1 x Parallel (SPP/EPP/ECP)	
	1 x Speaker-out, 1 x Line-in & 1 x MIC-in, Built-in Speakers	
Expansion Slot	2 x PCI	2 x PCI
Power Supply	ATX 180w, 100~240VAC @ 50~60Hz	ATX 180w, 100~240VAC @ 50~60Hz ,
Construction	Heavy-Duty Steel (IP65)	
Front Bezel	Big bezel, Small bezel, Aluminum bezel black/silver gray (option)	
Chassis Color	White / Black	
Mounting	Panel mounted	
Dimensions/ Weight	12.1" : 392.2 x 299 x 96.2 mm (W x H x D), 8.4 kg (bare bone) (Small Bezel) 15" : 407.71x 331.49 x 98 mm (W x H x D), 9.4 kg (bare bone) (Small Bezel) 17" : 445.2 x 377.6 x 101.2 mm (W x H x D) , 11.5 kg (bare bone) (Small Bezel) 19" : 483.51 x 408.13 x 104.2 mm (W x H x D) , 13.6 kg (bare bone) (Small Bezel) 12.1" : 432.2 x 335 x 98.2 mm (W x H x D), 8.4 kg (bare bone) (Aluminum Bezel) 15" : 447.71 x 371.09 x100 mm (W x H x D), 9.4 kg (bare bone) (Aluminum Bezel) 17" : 485.6 x 418 x 103 mm (W x H x D) , 11.5 kg (bare bone) (Aluminum Bezel) 19": 523.91 x 448.53 x 106 mm (W x H x D) , 13.6 kg (bare bone) (Aluminum Bezel) 12.1" : 432.2 x 335 x 96.2 mm (W x H x D), 8.4 kg (bare bone) (Big Bezel) 15" : 447.71 x 371.09 x 98 mm (W x H x D), 9.4 kg (bare bone) (Big Bezel) 17" : 485.6 x 418 x 101.2 mm (W x H x D) , 11.5 kg (bare bone) (Big Bezel) 19" : 523.91 x 448.53 x 104.2 mm (W x H x D) , 13.6 kg (bare bone) (Big Bezel)	
O/S	Windows 2000, XP	
Safety	CE , FCC	

Imported & Distributed in Australia By:



Rev : 1.01