

THERMAL PRINTER

CITIZEN®

CBM-270



CBM-270

Features

- Palm size
- Lightweight
- Availability of wall mount
- Paper auto loading
- Bar-code printing
- Compatibility (ESC/POS*)
- Paper near end sensor
- 2K bytes input buffer
- Label printing (option)
- Black & red printing with special paper (option)

Applications

- POS
- Banking
- Medical equipment
- Coupon
- Ticket
- Daily report
- Delivery
- Bar-code

Specifications

Printing method	Line thermal dot printing
Printing width	48mm (384 dots/line)
Dot pitch	8 dots/mm
Printing speed	Aprx. 11 lines/sec. (max.)
Number of columns	Font A: 32 col. Font B: 42 col.
Font	Font A: 12 x 24 Font B: 9 x 24
Emulation	ESC/POS™
Bar-code type	UPC-A/E, JAN(EAN), ITF, CODABAR, CODE39, CODE128
Line spacing	4.23mm (1/6 inches)
Printing Paper	Thermal roll paper: 58mm x 83ø(max.)mm Thickness: 60 – 75µm Thermal label paper: 58mm x 83ø(max.)mm Thickness: 150µm Label width: 56mm (max.) Label length: 25mm/pc (min.)
Interface	Serial (RS-232C) or Parallel (Centronics)
Input buffer	2K bytes
Power supply	DC 7.2V2A (Peak 6A) or AC adapter AC100 – 240V (27AD)
Weight	Aprx. 600g
External dimensions (W x D x H)	106 x 184 x 110mm
Reliability	Print head life: (25°C) Head: 50,000,000 pulses (12.5% printing), 50km
Safety standard	FCC class A, TUV-GS, CE marking

*ESC/POS is a trademark of Seiko Epson Corporation.

Japan CBM Corporation

Information Systems Division
5-68-10 Nakano, Nakano-ku, Tokyo, 164-0001 Japan
Tel: (81)-3-5345-7540
Fax: (81)-3-5345-7541
<http://www.jcbm.co.jp/>
e-mail: info-sys@jcbm.co.jp