Chromebase Mini

Smaller Surface. Superior Service.
Commercial Grade Chrome Base 10" All-in-One Multi-Touch Solution.

Introducing the Chromebase Mini 10'' Multi-touch solution, an ultra-thin and powerful device specifically designed for commercial and corporate usage, with a high-touch experience

The Chromebase Mini is a solid-state interactive solution designed to be extremely reliable and secure, making it ideal for interactive public displays in high traffic environments (i.e. as a digital signage, POS, kiosking, meeting room management or corporate environments).

Chrome Device Management allows administrators to manage their organization's Chrome devices from a single place. Integrators can also use the signage app of their preference available via the Chrome Web Store to control what's on the screen.

The advantages of the Chromebase Mini 10".
- A commercial grade multi-touch, all-in-one solution
- Tough and tamperproof design for 24/7 operability in public spaces
- High quality camera and speakers that meet Chrome video conference and Hangouts Requirements
- Wide viewing angles in landscape and portrait
- Multiple mounting options: recessed surfaces, wall mounts and kiosks.
- Optional Chrome Device Management to save valuable time, installation cost, programming and maintenance.

29.9 mm

Remove I/O Cover

Audio Combo Jack | HDMI Port | LAN Port | Power Input | USB2.0 with BC1.2

Chromebase Mini 10"

Specifications

Features	Enterprise Ready Grade all-in-one multi-touch solution with Chrome OS. Operating temp <40°C/104°F, shockproof, fanless, and solid state, front panel water resistant, for commercial environments, APAR (AC Power Auto Recovery)		
Operating System	Chrome OS		
CPU	Rockchip RK3288C Quad-Core Cortex-A17 turbo up to 1.8GHz		
Graphics	ARM Mali-T764 MP4 GPU @ 600 MHz		
Memory	Dual Channel 4GB, LPDDR3		
Chassis	IPX2 Compliant incl. cable cover		
	SECC material - fanless design		
Panel & Touch Panel	AHVA Panel 10.1" (1280x800) 250 Nits Support 10 points (PCT Multi Touch) IP54 dust and water protection		
LAN	Gigabit Ethernet [RJ45]		
Audio	Maxim MX98090 Build in stereo digital mic. and speaker		
Storage	EMMC 5.0, 16 GB		
Form Factor	Dimensions (WxHxD)	270 x 179 x 29.9 mm 10.63 x 7.05 x 1.18 inch	
	Weight	1.22 kg 2.69 lbs	
	Color	Gun-metal black	
Networking	Giga LAN Realtek RTL8211E-VB with LED indicate Wi-Fi+ Bluetooth; Wireless 802.11 b/g/n/ac+BT4.0 build in 2.4/5 G Embedded Antenna		

Front Pannel		10.1" native resolution 1280x800 250nits Internal Stereo Digital MIC	
Warranty		The Chromebase Mini comes with a 1 year warranty. Extended warranty optional for 3 years	
Rear Panel I/O	USB 2.0 port	support BC1.2 x 3	
	HDMI output	x 1	
	RJ45 LAN	x 1 10/100/1000 Mb	
	Audio Combo Jack	x 1 (Mic/ earphone)	
	Power switch	x 1 (Hidden Type)	
	Wide Votage Range DC input	DC 12~60V power inlet Jack x 1	
Video I/O		FHD Webcam (2M Pixel)	
Accessories		User Manual, Warranty and Support Card, Power Cord, Cable Cover (Knock-out Design), On/off pin tool Bundle Desktop stand for landscape and portrait mode, cable clamp tie	
Optional Accessories		VESA wall mount Various bases and mounts	
VESA		VESA hole: 75 x 75, 50 x 75 Cable clips protect and route cables Flexible cable cover knock-out design	
Environment	Operating temperature	0°C ~ 40°C 32°F ~ 104°F	
	Non-Operation Temperature	-20°C ~ 60°C -7°F ~ 140°F	
	Relative Humidity	90%@50°C	
	IP54 (front) fanless design, IPX2(rear) compliance		

For more information on Chrome Mini products, visit us at www.aopen.com/chrome

Authorized Australian Distributor: Goodson Imports Pty Ltd, Representation in all main States and New Zealand, Head Office: 9 Liberty Road, Huntingwood NSW 2148, Sydney Australia Ph: 02-8875 4544 Fax 02-8875 4588, www.goodson.com.au