

THERMAL PRINTER

CT-S300

High Speed Thermal Printer

NEW

CITIZEN



AC adapter type



Vertical solution



built-in AC adapter type

* color: cool white

Features

- 100mm/sec. High-speed
- Paper-drop-in style
- 80 or 58 mm paper width
- Bit map data registration
- Cash drawer kick-out
- *ESC/POS compatibility
- Bar-code printing

Applications

- Receipt
- Coupon
- Ticket
- Daily report
- Kitchen
- Delivery slip
- Bar-code

Specifications

Printing method	Line thermal dot printing
Printing width	80 mm paper: 72mm/576 dots
Dot pitch	8 x 8 dots/mm (203 dpi x 203 dpi)
Printing speed	Max. 100mm/sec. (800dot-lines/sec.)
Number of columns	Font A: 48 columns, Font B: 64 columns, Font C: 72 columns
Character size(W x H)	Font A: 1.5 x 3.00mm, Font B: 1.13 x 2.13mm, Font C: 1.00 x 2.00mm
Character table	Code page 437, 850, 852, 857, 860, 863, 865, 866, Katakana, Windows code
Bar-code type	UPC-A/E, JAN-13/8, ITF, Code 39, Code 128, CODABAR, Code 93
Line spacing	4.23mm (1/6 inch), can be set by a command
Paper	Paper width, 80mm x ϕ 83mm Thickness: 0.065 - 0.075mm
Interface	Parallel: IEEE 1284 and Centronics compliant, Serial(RS-232C)
Input buffer	4K bytes
Drawer kick-out	2 drawers
Power supply	DC24V $\pm$ 7%
AC adapter	Input: AC 100-230V, 1.3A Output: DC24V, 2A
Weight	Approx. 1.2kg
Dimensions(W x D x H)	145 x 195 x 121 mm
Operating environment	5 - 40°C, 35 - 85% RH
Storage environment	-20 - 60°C, 10 - 90% RH
Reliability	Thermal head: 100,000,000 pulses or 100km Cutter: 1,000,000 cuts
Safety standard	UL, C-UL, FCC class A, TUV-GS, CE marking

Japan CBM Corporation

Information Systems Division
5-68-10 Nakano, Nakano-ku, Tokyo, 164-0001 Japan
Tel: (81)-3-5345-7540
Fax: (81)-3-5345-7541
<http://www.jcbm.co.jp>
e-mail: info-sys@jcbm.co.jp

*ESC/POS is a trademark of Seiko Epson Corporation.
All specifications are subject to change without prior notice.

Printed in Japan