

DSD42-HE Spec

Specifications

42" panel
 Dimension (set) : 962x 555x 52 mm
 Dimension (Package): 1083x 675x 230 mm
 Slim Bezel : 11.8 mm
 Weight (Gross\Net) : (20.3Kg \ 16.7Kg)
 Display Orientation : Landscape \ Portrait
 Mounting: wall mount (VESA FDMI) : 400x300

LCD Panel

Resolution : 1920x1080
 Pixel pitch : 0.4845 x 0.4845
 Brightness : 500 nits
 View angle :178/178
 Contrast ratio : 4000:1
 Response time (average) : 8ms

Features

Zoom and shrink scaling (all resolution from VGA to SXGA)
 Auto Detection/Auto calibration, Scaling
 Speaker line out : 8Wx2
 OSD support
 Keypad Control \ IR Remote Control
 Thermal alarm and auto protection

I/O Port

AC inlet x1 \ AC outlet x1
 Audio inx2 \ Audio out x1
 Speaker line out R/L
 D-sub (VGA) in x 2
 HDMI x2
 RS232 in x1 \ RS232 out x1



AC Input \ Output

AC Input : 100~240VAC; 110W Max.
 (Not Include AC output 400W)
 AC Output: 100~240VAC, 400W (Max)

Touch screen (Optional)

None

Temperature

Operating 0 to 40 °C
 storage: -20 to 60 °C

Humidity

80% R.H. max

Australian Authorised Distributor: Goodson Imports Pty Ltd,
 Offices in all main States and New Zealand
 Head Office: 142 Wicks Road, North Ryde NSW 2113, Sydney Australia
 Ph: 02-8875 4544 Fax 02-8875 4588, www.goodson.com.au