

PRODUCT PICTURE

Applications

Fanless design is particularly suitable for noise-free environment, such as hospitals, cafeterias, museums, pharmacies, resorts, luxury stores, etc.

Key Features

- Fanless Design
- Easy Maintenance
- Light Weight
- Wide Ranges of Tilting Angles
- Dustproof
- Wall Mountable



System Specifications

System

- CPU: Support VIA Eden™ Processors 1GHz
- Memory: 2 x 240 pin DDR2 RAM slot up to 2GB, supports DDR2 533/400
- Chipset: VIA CX700 Chipset
- Graphics: - Built-In Core Logic, AGP 8X, Share with system memory (Up to 128MB)
- Support Dual Display Mirroring/Multiple Mode.
- Network: 10/100/1000 Base-T fast Ethernet
802.11g Wireless LAN (Optional)
56K hardware Modem (Optional)
- Audio: VIA HD Codec VT1708 (Line-out, Mic.)
- Power Supply: DC 19V~24V power input
- OS: Windows 2000/XP/XPE, WEPOS
- Key Lock: Front I/O key lock x 1
- LED: Power, LAN, HDD

I/O Ports

- USB: 6 x USB 2.0 (4 x Rear IO, 2 x On Board Pin Header)
- Serial Ports: 3 x DB-9 (COM 2, 3, 4)
COM 1 is reserved for touch panel
+5V/12V Selectable on pin 9
- LAN: 1 x RJ-45 interface
- PS/2: 2 x PS/2 ports (For keyboard and mouse)
- Audio: 1 x Mic in / 1 x Line-out
- VGA: 1 x DB-15 VGA interface for dual display
- Modem: 2 x RJ11 Phone Jack Modem
- Cash Drawer: 1 x RJ11 for DC12V cash drawer

Physical Dimensions

- Display Tilting angle: -10°~85°
- Weight: 8.1 Kg
- Dimension: 367(W) x 323(D) x 340 (H) mm

Display

- LCD: Com-POS 15"G15" TFT
- Max. Resolution: Com-POS 15"G1024 x 768
- Brightness: Com-POS 15: 250 cd/m²
- Touch Screen: 5-wire Analog resistive (ELO, E-Turbo)

Environment

- EMC & Safety: CE, FCC
- Temperature: Operating: 0 ~ 40°C
Storage: -20 ~ 60°C
- Humidity: 10% ~ 90%

Storage

- HDD: 1 x 2.5" S-ATA or IDE Hard Disk drive on pedestal (Optional)
- Card reading: 1 x Slim type 6 in 1 Card reading drive (Optional)
- CF: 1 x Compact Flash type I/II socket (Optional)

Optional Items

- Memory: DDR2 256MB, 512MB, 1GB (DDR2 533, 240Pin)
- HDD: 60 GB, 80GB (2.5", S-ATA, 5400RPM)
- Compact Flash: Built-In Compact Flash Readers
- Card reading: Slim type 6 in 1 Card reading drive
- W-LAN: 802.11g Wireless LAN module
- Modem: 56K hardware Modem
- MSR: Track 1/2/3 Magnetic Stripe Reader
- Customer Display: VFD Customer Display
LCD Customer Display
- OS: Windows 2000/XP/XPE, WEPOS

Australian Distributor:

