

IMPACT PRINTER

CITIZEN®

iDP-460



iDP-460

Features

- Compact design
- Metal tear bar
- Two color printing
- Compatibility with most bankcard terminals
- Mini DIN interface model (iDP-460VF)
- Paper end sensor
- Paper auto loading
- Cash drawer kick out

Applications

- Receipt
- Ticket
- Credit/Debit
- Kitchen
- Delivery

Specifications

Printing method	Serial dot impact
Printing direction	Bi-directional
Font	7 x 7 matrix
Number of columns	40/42 columns
Printing speed	3.0 lines/sec.
Character size (W x H)	1.31 x 2.4mm
Line spacing	4.23mm or 2.82mm Min. 1.41mm
Character pitch	1.52mm
Line feed speed	30 lines/sec.
Interface	Parallel: Certronics, Serial: RS-232C, Current loop
Paper	76mm roll paper
Input buffer	250 bytes
Paper end detection	Equipped
Ink ribbon	Exclusive ink ribbon cartridge IR-41
Power supply	AC adapter 100/120/230
Power consumption	30W
Weight	Main: 1.25kg AC adapter: 0.95kg
External dimensions (W x D x H)	144 x 233 x 121mm
Operating temp. range	0~40°C
Storage temp. range	-20~60°C
Reliability	MCBF 2.5 million lines 80 million characters
Safety standard	UL, C-UL, FCC class A, TUV-GS, CE marking

Japan CBM Corporation

Information Systems Division
5-68-10 Nakano, Nakano-ku, Tokyo, 164-0001 Japan
Tel: (81)-3-5345-7540
Fax: (81)-3-5345-7541
<http://www.jcbm.co.jp/>
e-mail: info-sys@jcbm.co.jp