

KS-7210

www.posiflex.com

POSIFLEX
Your Success is Our Vision



Specification	KS-7210
Processor	Intel Pine View D525 1.8 GHz / 1 M cache CPU (Dual Core)
System Memory	DDR3 800 MHz, SO-DIMM socket x 1, max 4 GB, default 1 GB
Storage Device	2.5" SATA HDD or CF kit (Optional) or SSD kit (Optional)
Power Supply	12V DC power adaptor, 50 W
Audio	Line out
OS Support	Win 7 / Win XP Pro / POSReady 7 / POSReady 2009 / Win CE / Linux
Color	Black
Display	
LCD Display	10.1" TFT LCD, 1024 x 768 resolution
Touch Function	Resistive, 5-Wire, USB Interface
Brightness Control	Yes, by software control
Tilt Adjustment	From 20° to 90°
Connectivity	
LAN Port	10 / 100 / 1000 Mb
Parallel Port	Yes, special converting cable (Optional)
Serial Port	3, RJ-45 x 1 (Optional cable RJ-45 to DB9), DB9 x 2, with 5V support on Com1 / Com2 / Com3
Standard USB Port	4
CF Card Slot	Yes, type I, memory card only
CR Port	1, control 2 CR
Physical Dimension	
Dimension (W x D x H in mm)	260 x 205 x 266
Weight (N. W. in kg)	3
Environment	
Operation Condition	0°C ~ +40°C, 20%RH - 90%RH (Equipped with HDD) 0°C ~ +50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH
Options	
MSR	3 tracks and JIS-II
Wireless Lan	WiFi 802.11 b / g / n
CF Card	Type I card
SSD	8 GB minimum
VGA Port	D-SUB 15 pins, special converting cable
Wall Mounting Kit	WB-6812
KP-450	45-key programmable keyboard
PD-309 / 309U	2 x 20 LCD, default 200 mm pole
PD-2605 / PD-2605U	2 x 20 VFD, default 200 mm pole
2nd Display	12" LM-2312, 10" LM-2310
Certifications	

KS-7210

Midrange Small FanFree POS Terminal



Design and Manufacturing In Taiwan by Posiflex Technology Inc.
** The product information and specifications are subject to change without prior notice.

2012 KS72Q3C1

POSIFLEX Posiflex Technology, Inc.
Headquarters
No.6, Wuquan Rd., Wugu Dist., New Taipei City
248, Taiwan (R.O.C.)
Tel: +886 2 2299-1599 Fax: +886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller

www.posiflex.com

KS-7210

Posiflex introduces the fanfree KS-7210 as a midrange small POS terminal.

The KS-7210 features built-in MSR function in its compact case. The integrated design not only enhances the convenience of cashier's operation but also neat look. It may be small but can be a big deal, supporting up to Intel 1.8 GHz CPU, DDR3, and 10" touch screen. The KS-7210 brings better performance with accessories like the easy-to-reach side programmable keypad that raises the efficiency of input, the wall mounting kit that raises the flexibility of deployment, the customer pole display that raises the visibility of promotions, and so on.

The KS-7210 fits small and medium retailers by its powerful performance and extendibility.



Key Features

- ▶ Equipped with Intel Pine View D525 Dual Core 1.8 GHz CPU and DDR3 memory
- ▶ SSD or CF card for more storage options (Optional)
- ▶ Resistive touch screen, 10.1" LCD monitor 800 x 600 resolution
- ▶ Fanfree design boasting quiet and anti-dust features
- ▶ Aluminum die casting design for efficient cooling
- ▶ Push-open cover to protect power switch from accidental shutdown
- ▶ Rear bottom cable cover for safety and neat outlook
- ▶ Adjustable LCD tilt angle from 20° to 90° for flexible operation
- ▶ Built-in MSR function (Optional)
- ▶ Side mounted programmable keypad (Optional)
- ▶ Wall mounting option (Optional)

