



NCR RealPOS™ 5964 Performance Touch

Easy to Use
Flexible, Durable



- Robust Capacitive Touch
- Superior Viewability
- Outstanding Retail Functionality

Durability to Last

Designed for a variety of retail environments, the NCR RealPOS 5964 performance touch display maximizes store productivity and ensures the highest levels of customer satisfaction. The display uses retail designed capacitive touch technology that provides superior usability and proven durability. The screen offers increased resistance to common retail contaminants, such as dirt grease, water, coffee, vinegar, cleaning detergents and gasoline. Additionally, the NCR RealPOS 5964 performance touch display utilizes dual-bulb backlight technology for longer lasting performance and industrial LCD panels for longer life, supportability and design stability.

Open Systems Drive Flexibility and Investment Protection

Whether you use a Microsoft® Windows® or Linux operating system, NCR's industry standard OPOS and JavaPOS drivers support most applications and operating systems. NCR also leverages industry standards for connectivity, which provides you with seamless integration into your current point-of-service environments. NCR RealPOS performance touch display utilizes VGA for video connections and USB for touch communications. For added flexibility, the NCR RealPOS performance touch display features an additional peripheral port to connect a hand-held scanner or keyboard.

Built Tough for Retail

The rigorous, real-world of retail puts strain on displays that run ten plus hours a day. Screens run non-stop and a daily average of five or more employees tap, punch, lean on and otherwise abuse POS touch screens. With quality and reliability in mind, the NCR RealPOS performance touch display undergoes comprehensive environmental and compatibility testing and is manufactured under strict NCR standards to provide you with confidence that your touch display will keep working despite mishaps at the checkout.

For more information, visit www.ncr.com, call 866.431.7879, or e-mail retail.contactus@ncr.com.



NCR RealPOS™ 5964

Performance Touch

Technical Specifications:

Display

- Display type: High bright active matrix color LCD
- Display resolution: XGA (1024 x 768)
- Resolutions supported: VGA, SVGA, SXGA
- Display back-light: Dual bulb back-light
- Back-light life: 50,000 hours to half brightness
- Brightness with touch: Capacitive: 315 typical
- Contrast: 400:1

Touch Technology

- Capacitive

Connectivity

- Video interface: VGA or DVI
- Touch interface: USB
- Power: Powered USB or power brick
- Additional ports: 2 x USB keyboard or scanner port

Features & Options

- MSR: 3-track ISO optional
- Speakers: Integrated stereo speakers standard
- Remote mount: Yes (VESA compliant)
- Integrated mount: For NCR RealPOS 80_{XRT}
- Wall mount
- Software Drivers: OPOS, JavaPOS
- Flashable firmware via USB

Physical Specifications

Dimensions (WxDxH)

- without mount: 13.75" x 3.25" x 13"
- with mount: 14.5" x 10" x 13.75"
- Beige or charcoal
- VESA mount compatibility
- Operating range: Temperature: 5 to 45° Celsius, Relative humidity: 10-90%

Note: 12" Powered RS-232 Model not generally available



NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions, and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

NCR RealPOS is either a registered trademark or trademark of NCR Corporation in the United States and/or other countries. All brand and product names appearing in this document are trademarks, registered trademarks, or service marks of their respective holders.