

# PS-3315E

# POSIFLEX

## Slim and Flexible

Streamlined design equips with a foldable base; PS-3315E provides users with unmatched flexibility to adjust the screen to a height and angle depending on the application.

## Expandable and Neat

Designed to better manage peripheral connectivity by separating a full set of ports into the top of the terminal top and the base, PS-3315E ensures neat, reliable peripheral cabling.

Specification	PS-3315E
Processor	Intel J1900 processor, 2.00GHz/2.42GHz (Burst), 1M cache
System Memory	DDR3L 1333MHz SO-DIMM x 1, max. 4GB
Storage Device	1 x SATA + 1 x eMMC connector, 64GB SATA SSD default
Power Supply	12V/30W
OS Support	Windows 10 IoT/Windows Embedded 8.1 Industry/Windows 7/PCSRReady 7/Linux per request

Display	
LCD Display	15" TFT LCD, 1024 x 768 resolution
Touch Function	5-wire resistive touch

Connectivity	
LAN Port	10/100/1000Mb x 1
Serial Port	3 x DB9 + 1 x RJ45, 5V/12V support on all COM ports
Parallel Port	1, via optional conversion cable
UPS Port	N/A
Standard USB Port	5
PS/2 Port	1, via optional conversation cable
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable
Audio	Buzzer only
WiFi	Optional internal mini-PCIe WiFi module with PIFA Antenna

Physical Dimension	
Dimension (W x D x H in mm)	372 x 320 x 252.7
Weight (N.W. in Kg)	5.86

Environment	
Operation Condition	0°C - 40°C, 20%RH - 90%RH [Equipped with HDD]; 0°C - 50°C, 20%RH - 90%RH [Equipped with SSD]
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

Options	
SA-105	Side Attachment for PS Series with 3 track MSR
SA-205	Side Attachment for PS Series with iButton
SA-305	Side Attachment for PS Series with support for 3 track MSR, RFID and Finger Print Sensor
SA-405	Side Attachment for PS Series with support for 3 track MSR, 3G dongle and Finger Print Sensor
SA-505	3-in-1 attachment with MSR (default), RFID & iButtonsupport for 15"/17" XT series & 15"/15.6" PS series
LM6807U/LM6810U	7" 800 x 480 / 10" 1024 x 768 rear-mount 2nd display for PS series (USB interface)
PD-2609UE	2 x 20 VFD, rear-mount, USB with Virtual COM support
PD-360UE/PD-360R	2 x 20 LCD, rear-mount, USB with Virtual COM support (PD-360UE)/RS232(PD-360R)
PD-6807U	7" color LCD graphical line display, rear-mount (USB interface)
KP-500	40-key dynakey attachmentwith MSR or RFID option for 15"/17" XT series & 15"/15.6" PS series

\* The product information and specifications are subject to change without prior notice.  
\* Please refer to the web site for more attachment options.

US Patent 9004436

## A Robust, Economical Choice



## PS-3315E Best Value Fanless POS Terminal

PS-3315E is a 15" touch screen fanless POS Terminal with all the essential functions and capabilities to satisfy businesses of all sizes, and represents one of the best value choices in the entry-level POS Terminal segment.

Certifications



Design and Manufacturing in Taiwan by Posiflex Technology Inc.

The product information and specifications are subject to change without prior notice.

2016Q1

# POSIFLEX

POSIFLEX TECHNOLOGY INC.  
No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan  
Tel : +886-2-2299-1599 E-mail : sales@posiflex.com.tw  
Fax : +886-2-2299-1819 www.posiflex.com

Authorised Australian & New Zealand Distributor:  
Goodson Imports Pty Ltd  
9 Liberty Road  
Huntingwood NSW 2148  
Representation in all main States and New Zealand  
Ph: 02-8875 4544 Fax 02-8875 4588  
www.goodson.com.au