

POSIFLEX



Make Your Business Look More Attractive

RT-2015-G2/2016-G2

Fanless POS Terminal

RT-2015-G2/2016-G2

The RT-2000-G2 Series radiates in its new design – featuring an ultra-slim and sleek look that exhibits elegance. It is uncompromising to the space requirements and provides better cable management and easy maintenance. The new RT-2000-G2 Series is taking POS terminal design into the next level, setting your brand image apart from the others.



Full HD
15.6"

Slim & Stylish Look

With stylish, fluid contours for its base and true-flat design, the RT-2000-G2 Series has 15" or 15.6" PCAP touch screen, and full suite of ports that are hidden in the clean rear cover. No screws can be found on its surface maintaining a neat and sleek look.

Patented Fanless Technology

The patented fanless technology allows the terminal to run quietly in all kinds of harsh conditions and – at the same time - provides a long service life.



Fanless
Technology



Dust
Resistant



Water
Resistant



Money
Saving





Clean Cable Management

Advanced cable management design delivers a truly clutter-free station. The standard base can house the optional PoweredUSB or USB extension module, while the optional base integrates a UPS backup (RB-5000) for the event of a power failure.



Expandable
USB Module



Serviceability & Shipment with Ease

Rear cover can be removed easily and without tools, thus allowing for faster installation and serviceability. The unit can be shipped with line display or 9.7" / 10.1" 2nd customer facing LCD display attached and folded, saving deployment time as well as shipping costs.

RT-2015-G2/2016-G2

Specification	RT-2015-G2	RT-2016-G2
Processor	Intel Elkhart Lake Celeron J6412, up to 2.60 GHz, 1.5M Cache	
System Memory	DDR4 SO-DIMM x 2, max. 32GB	
Storage Device	M.2 connector [SATA Signal Only] x 2	
RAID Function	N/A	
Intel vPro Support	N/A	
TPM Support	Yes, TPM 2.0	
Power Supply	12V/60W	
OS Support	Win 10 IoT 64 bit	

Display & Touch

LCD	15" TFT LCD	15.6" TFT LCD
Resolution	1024 x 768	1920 x 1080
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)	

I/O & Expansion

Serial Port	3, DB9 x 1 + RJ45 x 2, 5V/12V support on all COM ports	
Standard USB Port	5, USB 3.0 x 2 + USB 2.0 x 3	
PoweredUSB Port	Optional Powered USB module with 24V + 12V (USB 3.0 x 1 will no longer be available with the Powered USB module)	
OTG USB	N/A	
LAN Port	10/100/1000 Mb x 1	
Display Port	VGA via proprietary connector (12V support for Posiflex monitors) x 1 + mini DP x 1	
CR Port	1, control 2 CR via optional Y-cable, supporting 24V cash drawer	
Audio	Internal 2W speaker x 1	
Expansion Slot	M.2 slot x 1	

Physical Dimension

Dimension (W x D x H in mm)	368 x 207 x 325	402 x 207 x 297
Weight (N. W. in kg)	5.4	5

Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	-20°C - 70°C, 10%RH - 90%RH	

Built-in Options

WiFi	M.2 WiFi/BT module	
Camera	1MP wide angle camera	
AG Glass	Cannot coexist with built-in camera	

Attachment Options

POS Monitor	Non-touch TFT LCD: 9.7"/10.1"/15"; PCAP touch TFT LCD: 9.7"/10.1"	
Line Display	2 x 20 rear-mount VFD customer line display	
External UPS Pack For RT Series	UPS battery module (12V/2300mAh)	
Attachment	MSR; iButton; 2D Scanner; RFID; Fingerprint Sensor	

* Designed and Manufactured in Taiwan by Posiflex Technology, Inc. * Please refer to the website for more attachment options.

* The product information and specifications are subject to change without prior notice.

Certifications 	POSIFLEX TECHNOLOGY, INC. No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw Fax : +886-2-2268-5388 www.posiflex.com		EN20220711V4 Authorized Distributor / Reseller
			