

TX-3700 Series

www.posiflex.com



Key Features

- ▶ 2 x Powered USB ports (1 x +12V, 1 x +24V)
- ▶ Intel D2550 1.86GHz Cedarview dual core CPU and DDR3 memory
- ▶ Advanced FanFree design
- ▶ Compact size and wall-mount capability for flexible deployment
- ▶ Optional 2nd VGA port
- ▶ Wide range of I/O support for various applications

Specification	TX-3700
Processor	Intel Cedarview dual core D2550 CPU, 1.86GHz, 1M Cache
System Memory	DDR3 1066MHz, SO-DIMM x 1, max. 4GB, default 2GB
Storage Device	2.5" SATA HDD or SSD (optional)
Power Supply	12V DC power adaptor, 150W
OS support	Windows 7 32bit / Windows XP Pro / POSReady 7 32bit / POSReady 2009 / Linux
Connectivity	
LAN Port	10 / 100 / 1000Mb
Serial Port	DB9 x 3 with 5V/12V support on COM1 / COM2 / COM3
Standard USB Port	4
Powered USB Port	2, 1 x 12V and 1 x 24V
VGA Port	D-SUB, 15 pins, with 12V support for Posiflex monitor
CR Port	1, control 2 CR
Physical Dimension	
Dimension (W x D x H in mm)	270 x 253 x 86 (TX-3700); 270 x 200 x 86 (TX-3700S)
Weight (N. W. in kg)	2.17
Environment	
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH
Options	
SSD	8GB minimum
COM4	DB9, with 5V support, cannot coexist with 2nd VGA port
2nd VGA Port	Yes, cannot coexist with COM4
Wall Mounting Kit	WB-6812
Note	
<ul style="list-style-type: none"><li>• Intel Cedarview CPU does not support 64 bit OS, therefore POSReady 7 64 bit and Windows 7 64 bit are not supported on TX-3700.</li><li>• Current Intel XP Pro / POSReady 2009 graphics driver for Cedarview platform does not support dual display. Update may be available in Q3.</li></ul>	

Certifications

Design and Manufacturing In Taiwan by Posiflex Technology Inc.

\*\* The product information and specifications are subject to change without prior notice.

2012 TX37Q2C1

TX-3700 Series

Feel the Power of Powered USB



Is space a premium for you? Are there simply too many power adaptors laying around that you wish you can make them disappear with a wave of a hand? Posiflex has a solution for you!

Packed in a compact enclosure with four standard USB ports are two additional Powered USB ports. Powered USB port allows USB devices such as a receipt printer and electronic weight scale to draw power directly from the port without the cumbersome power adaptor. No power adaptor equals tidy counter space!

TX-3700 combines the convenience of Powered USB with the powerful Intel Cedarview dual core CPU in an advanced FanFree design, making it one of the best compact POS Box solutions available!

TX-3700 offers flexible deployment for space-sensitive retailers

Posiflex Technology, Inc.

Headquarters

No.6, Wuquan Rd., Wugu Dist., New Taipei City  
248, Taiwan (R.O.C.)  
Tel: +886 2 2299-1599 Fax: +886 2 2299-1819  
sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller

www.posiflex.com