

# **FORTIS**

## **XP-2000 Series**



Clear LED indicator panel



### **Printer**

2" thermal printer (60mm/sec)



### **MSR**

2 or 3 tracks & JIS-II

Posiflex now present a whole new generation POS terminal, which is a combination of touch screen, printer, MSR, and the most reliable FanFree structure. This integrated solution of XP-2000 series not only uncomplicated, but also carrying a brilliant performance to user in order to face the busiest situation.

XP-2000 series suit for small to medium retailer and other segmentations of market.

### **Features**

- All-in-one integrated system with touch screen, thermal printer and MSR that cleans up the counter space of all the unsightly wirings.
- Fan-free design with aluminum die casting structure ideally suited for both harsh and quiet environment.
- Integrated thermal printer featuring "One-button cutter blade retract" design. It is achieved by simply pushing the button to open the paper cover and automatically retract the cutter blade for easy paper jam removal. (excluding XP-2008H)
- User-friendly "drop-load" design for easy printer paper roll loading.
- High quality, rock solid build & design with ease of maintenance and serviceability in mind.



Real mount  
customer pole display



12" TFT LCD, 1024x768 resolution,  
LED Backlight, Support touch panel



Specification	XP-2012H	XP-2010H	XP-2008H
Processor	Intel Celeron M 600MHz,512K Cache CPU		
System Memory	DDR2 400MHz,SO-DIMM x 1, max 2G, default 512MB		
Storage Device	DOM 1GB or 2.5" SATA HDD (optional) or SSD kit(optional) or CF Kit(optional)		
Power Supply	12V DC Power adaptor, 60W		
Audio	Buzzer Only		
OS support	Linux, WinCE,WinXP PRO, POSReady(support XP & POSReady by upgrade to SSD or 2.5" SATA HDD)		
Display			
LCD	12" TFT LCD, 1024x768 resolution	10.4" TFT LCD, 800x600 resolution	8" TFT LCD, 800x600 resolution
Touch Function	Resistive, 5-wire, USB Interface		
Brightness Control	By software control		
Tilt Adjustment	From 14° to 55°		
Connectivity			
LAN Port	10 / 100 Mb		
Serial Port	DB9 x1,with 5V support		
Standard USB Port	4		
VGA Port	D-SUB 15 Pin, with 12V power for Posiflex LCD Monitor		
CR Port	1		
Printer			
2" Thermal Printer	60mm/sec, 58mm paper width		
Cutter	Auto Cutter		Manual Cutter,Auto cutter optional
Physical Dimension			
Dimension (W x D x H in mm)	325 X 386.2 X 331.2	325 X 386.2 X 298.1	325 X 386.2 X 249.6
Weight (N. W. in kg)	6.54	5.75	4.15
Environment			
Operation Condition	0°C - 40°C, 20%RH - 90%RH		
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH		
Options			
MSR	Integrated, 2 or 3 tracks and JIS-II		
PD-2605 / PD-2605U	2x20 VFD, default 200mm pole		
PD-2606U	2x20 VFD, rear mount		
PD-309 / PD-309U	2x20 LCD, default 200mm pole		
PD-330U	2x20 LCD, rear mount		
PD-76X4	240x64 dots Graphics LCD, default 200mm pole		
SSD	8GB Minimum		
2.5" SATA HDD	80GB Minimum		
LM-2208	N/A	8" TFT LCD, 800x600 resolution	
LM/TM-2212	12" 2nd LCD Display or touch LCD Display with attachment SD-300	N/A	
CF Kit	Board & Bracket & Cable		
CF Card	Type I Only		

◆The product information and specifications are subject to change without prior notice.

2010 V.04

## Posiflex Technology, Inc.

6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan  
Tel: 886 2 2299-1599 Fax: 886 2 2299-1819  
sales@posiflex.com.tw www.posiflex.com

Australian Distributor:  
Goodson Imports Pty Ltd  
142 Wicks Road  
North Ryde NSW 2113  
Offices in all main States and New Zealand  
Ph: 02-8875 4544 Fax 02-8875 4588  
[www.goodson.com.au](http://www.goodson.com.au)

